


Connection




- ⚠ Power Consumption: 12V@120mAh
- CVBS: Connect to analog VTX "CAMERA" port or "CVBS IN" port

Specifications

Image Sensor	Black&White Sensor
Horizontal Resolution	1500TVL
FOV	120°
Min.Illumination	0 Lux
WDR	Super WDR
LENS	M16/F1.0/2.8mm
Frame Rate	50/60fps
Power Consumption	<1.5W
Supply Voltage	5-20V
Output	PAL
Interface	Analog: CVBS
	HD: MIPI-CSI (Walksnail Avatar)
Latency	Average Latency 20ms
Image Quality	Allimage Enhancement


Dimensions




Unit: mm

CADDXFPV Support
email: support@caddxfpv.com

This content is subject to change. Download the latest version from
<https://www.caddxfpv.com>




安装连线



产品规格

图像传感器	黑白传感器
水平分辨率	1500TVL
FOV	120°
最小光亮度	0 LUX
WDR	Super WDR
镜头	M16/F1.0/2.8mm
帧频	50/60fps
功耗	<1.5W
电压	5-20V
制式	PAL
接口	模拟接口: CVBS 高清接口: MIPI-CSI (Walksnail Avatar)
延迟	平均延迟20毫秒
画面质量	AI画质增强

外形尺寸



C/ADDXFPV 技术支持
email: support@caddxfpv.com
此内容可能会修改, 从以下位置下载最新版本
<https://www.caddxfpv.com>