


Connection




- ⚠
- Power Consumption: 12V@120mA
 - CVBS: Connect to analog VTX "CAMERA" port or "CVBS IN" port

Specifications


Detector type	Uncooled Vanadium Oxide
Resolution	384x288@12um
Wavelength Range	8~14um
LENS	F1.0/9.1mm/48°(H)*34°(V)*59°(D)
Frame Rate	25/50 fps
Power consumption	<1.5w
Output	PAL
Supply Voltage	9V-24V
Temperature	-20°C~60°C
Interface	Analog Interface: CVBS
Latency	Average Latency 20ms
Image Quality	Allimage Enhancement

Dimensions




CADDXFPV Support
email: support@caddxfpv.com

This content is subject to change. Download the latest version from
<https://www.caddxfpv.com>




安装连线



产品规格

探测器类型	氧化钒非制冷红外焦平面探测器
分辨率	384x288@12um
波长范围	8~14um
LENS	F1.0/9.1mm/48°(H)*34°(V)*59°(D)
帧率	25/50 fps
功耗	<1.5w
输出	PAL
宽电压输入	9V-24V
温度	-20°C~60°C
接口	模拟接口: CVBS
延迟	平均延迟20毫秒
画面质量	AI画质增强

外形尺寸



CADDXFPV 技术支持
email: support@caddxfpv.com
此内容可能会修改, 从以下位置下载最新版本
<https://www.caddxfpv.com>